

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
9 September 2005 (09.09.2005)

PCT

(10) International Publication Number  
**WO 2005/083411 A1**

(51) International Patent Classification<sup>7</sup>: **G01N 27/20**,  
17/00, B02C 23/00

(21) International Application Number:  
PCT/CA2005/000285

(22) International Filing Date: 25 February 2005 (25.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/547,768 27 February 2004 (27.02.2004) US

(71) Applicant (for all designated States except US): **MCGILL UNIVERSITY** [CA/CA]; 845 Sherbrooke Street West, Montreal, Quebec H3A 2T5 (CA).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MARTINS, Sudarshan** [CA/CA]; 6887 Louis-Hebert Ave, Montreal, Quebec H2G 2H1 (CA). **RADZISZEWSKI, Peter** [CA/CA]; 41

Morgan, Baie d'Urfe, Montreal H9X 3A3 (CA). **BENSON, Coleman** [CA/CA]; 123 Laporte, Dollard des Ormeaux, Quebec H9A 3E3 (CA).


(74) Agents: **DUBUC, J.** et al.; Goudreau Gage Dubuc, Stock Exchange Tower, 800 Place Victoria, Suite 3400, P.O. Box 242, Montreal, Quebec H4Z 1E9 (CA).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: METHOD AND DEVICE FOR SENSING WEAR



(57) Abstract: A sensor for detecting erosion of a wear surface of a component, particularly a liner attached to the mill shell of a rotating grinding mill. The sensor comprises a conductive element embedded in the component, the conductive element comprising a first end positioned at a first distance from the wear surface, at least one conductive loop comprising a wear portion positioned at a second distance from the wear surface proximate to the first end and a circuit coupled to the at least one element for determining a continuity of the conductive loop.

WO 2005/083411 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*